



```
1  
2 --  
3 --  
4 --  
5  
6 SEL  
7 ( s  
8 A. *  
9 FRO  
10 whe  
11 and  
12 and  
13 and  
14 ord  
15 ;  
16
```

About

Run SQL Scripts
(32-bit)
Version: 1.1.7.2
Build id: 7422
October 18, 2017 12:39:43 PM MDT
C:\IBM\ACS\lacsbundle.jar

java.version: 1.8.0_152
java.vendor: Oracle Corporation
java.home: C:\Program Files (x86)\Java\jre1.8.0_152

Copyright(c) IBM Corporation 2012, 2017
All Rights Reserved

OK

SQL Formatter Settings

Keywords and built-in functions: Lowercase

Identifiers: Uppercase

Maximum line length: 200

Indent: 0

New lines

New line on comma: No new line

New line on AND/OR: No new line

New line on CASE keyword

Preview

```
select timestamp_format (case
when (substr('1400101', 1, 1) = '0')
then overlay('1400101', '19', 1, 1)
else overlay('1400101', '20', 1, 1)
end, 'YYYYMMDD')
as MY_TIME
from SYSIBM.SYSDUMMY1
```

OK Cancel

Before formatting

```
|SELECT
( select MESSAGE_TIMESTAMP
  from TABLE(QSYS2.HISTORY_LOG_INFO( (CURRENT_TIMESTAMP-8 hours), CURRENT_TIMESTAMP)) AA
  where AA.FROM_JOB = A.FROM_JOB and MESSAGE_TYPE = 'COMPLETION')- MESSAGE_TIMESTAMP,
A.*
FROM TABLE(QSYS2.HISTORY_LOG_INFO( (CURRENT_TIMESTAMP-8 hours), CURRENT_TIMESTAMP)) A
where 1=1
and MESSAGE_TYPE = 'INFORMATIONAL'
and FROM_USER = 'QSYSOPR'
and MESSAGE_TOKENS like '%CHECK%'
order by FROM_JOB , ORDINAL_POSITION
;
```

After formatting

```
5 select (select MESSAGE_TIMESTAMP
6         from table(QSYS2.HISTORY_LOG_INFO((current timestamp - 8 hours), current timestamp)) AA
7         where AA.FROM_JOB = A.FROM_JOB and MESSAGE_TYPE = 'COMPLETION')
8 - MESSAGE_TIMESTAMP, A.*
9 from table(QSYS2.HISTORY_LOG_INFO((current timestamp - 8 hours), current timestamp)) A
.0 where 1 = 1 and MESSAGE_TYPE = 'INFORMATIONAL' and FROM_USER = 'QSYSOPR' and MESSAGE_TOKENS like '%CHECK%'
.1 order by FROM_JOB , ORDINAL_POSITION
.2 ;
.3
```